# SEAT CAR Type: 264.3 | Bimz



#### **TECHNICAL SPECIFICATIONS:**

Length over buffer:	26 400 mm
Car body length:	26 100 mm
Car body width:	2 825 mm
Height above top of rail:	4 050 mm
Pivot spacing:	19 000 mm
Axle position:	21 500 mm
Axle position in the bogie:	2 500 mm
Bogie design:	Minden-Deutz 366
Tare weight:	41 t
Maximum speed:	200 km/h
First/second class seats:	-/60 plus 6 folding seats in the aisle
Compartments:	4 compartments 2nd class; 2 large compartments 2nd class
Air conditioning:	Sliding windows, no air conditioning
Toilets:	2, closed system
Washrooms:	-
Service room:	-
Service room: Brake design:	- <r> KE-GPR-Mg (D) [ep] [NBÜ]</r>
	- <r> KE-GPR-Mg (D) [ep] [NBÜ] <r>+Mg 103 t, <r> 71 t, R 66 t, P 48 t, G 39 t</r></r></r>
Brake design:	
Brake design: Brake weights:	<r>+Mg 103 t, <r> 71 t, R 66 t, P 48 t, G 39 t</r></r>
Brake design: Brake weights: Heating design:	<r>+Mg 103 t, <r> 71 t, R 66 t, P 48 t, G 39 t Whzes/Lhz</r></r>
Brake design: Brake weights: Heating design: Energy supply:	<r>+Mg 103 t, <r> 71 t, R 66 t, P 48 t, G 39 t Whzes/Lhz Central power supply</r></r>

#### **OUR FLEET:**

51 80 22 - 91 220-9	Bimz	264.3
51 80 22 - 91 229-0	Bimz	264.3
51 80 22 - 91 243-1	Bimz	264.3
51 80 22 - 91 254-8	Bimz	264.3
51 80 22 - 91 255-5	Bimz	264.3

### **ADDITIONAL INFORMATION:**

The cars can be used internationally according to the RIC standard and are compatible with 1000V, 1500V and 3000V traction current systems. They have 60 seats and an additional 6 large folding seats in the open-plan area.

RDC Asset has equipped all vehicles with new seats and power sockets as well as USB ports per seat. Optionally, we can provide a supply of Wifi.



## rdc-deutschland.de